



389.8.
2011

8

ISO 389-8:2004
Acoustics — Reference zero for the calibration of audiometric equipment —
Part 8: Reference equivalent threshold sound pressure levels for pure tones
and circumaural earphones
(IDT)



2012

27 2002 . 184- « — 1.0—2004 « », »

1 « - » (« 4 ») ,

2 358 « »

3 8 1 2011 . 671-

4 389-8:2004 « 8. »

«Acoustics — Reference for the calibration of audiometric equipment — Part 8: Reference equivalent threshold sound pressure levels for pure tones and circumaural earphones»).

1.5 (3.5).

5

« », « », « »

()

— ,

8000 16000 .
125 8000 . 389-5
125 16000 .
()
HDA 200.
SENNHEISER
-

Федеральное агентство
по техническому регулированию
и метрологии

Федеральное агентство
по техническому регулированию
и метрологии

Федеральное агентство
по техническому регулированию
и метрологии

State system for ensuring the uniformity of measurements. Acoustics. Reference for the calibration of audiometric equipment Part 8. Reference equivalent threshold sound pressure levels of pure tones for supra-aural earphones

— 2012—12—01

1

() , 125 8000 SENNHEISER HDA200. — 8—

2

389-1 1.

(ISO 389-1. Acoustics — Reference for the calibration of audiometric equipment — Part 1: Reference equivalent threshold sound pressure levels for pure tones and supra-aural earphones)

4869-1 1.

(ISO 4869-1. Acoustics — Hearing protectors — Part 1: Subjective method for the measurement of sound attenuation)

60318-1 1.

(IEC 60318-1. Electroacoustics — Simulators of human head and ear — Part 1: Ear simulator for the calibration of supra-aural earphones)

60318-2:1998 2. -

(IEC 60318-1:2009, Electroacoustics — Simulators of human head and ear — Part 2: An interim acoustic coupler for the calibration of audiometric earphones in the extended high-frequency range)

60645-2 2. (IEC 60645-2.

Audiometers — Part 2: Equipment for speech audiometry)

3

60645*2.

4

389-1,

4869*1.

60318*1

SENNHEISER HDA 200
60318*1 60318*2 (

1}

1.

HDA 200

(.).

(1).

21 *

25 * .

1—

	SENNHEISER 200		SENNHEISER 200
125	30.S	1500	5.5
160"	28.0	1600*	5.5
200"	22.0	2000	4.5
2S0	18.0	2500*	3.0
315"	15.5	3000	2.5
400"	13.5	3150*	4.0
500	11.0	4000	9.5
630*	8.0	5000	14.0
7S0	6.0	6000	17.0
800"	6.0	6300*	17.5
1000	5.5	8000	17.5
1250*	6.0		
4			
6	0.5		
4	/ 389-5.		

HDA 200

(10,0 ± 1.0)

145

130

()

200

(. [2]—()).

.1.

.1—

200

	12) 0 [4] (S) [6]				
	SENNHEISER 200				
	31	24	24	38	27
	62	24	24	38	27
/	17/14	13/11	15/9	15/23	13/14
	18 25				
	0.125; 0.25; 0.5; 0.7S; 1; 1.5; 2; 3:4:6	0.125 6.3 1/3- ; 0.75:1.5: 3:6	0.125: 0.25: 0.5:0.75; 1: 1.5: 2; 3:4.6	0.12S 6.3 1/3- ; 0.7S; 1.5: 3:6	
	60315-1				
	60318-1				

()

HDA 200

200

.1

-

4869-1

-

1/3-

[3].


.1 —

200

	*
63	16.S
12S	14.5
260	16.0
500	22.5
1000	28.5
2000	32.0
4000	45.5
8000	44.0
*	0.S

()

HAD 200



	<?,-< £. 6		6, - Gg.
125	- S.0	1250	-2.0
160"	-4.5	1600	-5.5
200"	-4.5	2000	-5.0
250	-4.5	2500	-6.0
315"	- 5.0	3150	- 7.0
400	-S.S	4000	- 13.0
500	-2.5	5000	- 14.5
"	-2.5	6300	- 11.0
600"	-3.0	8000	-8.5
1000	-3.S		
• 6	0.5		

[3].

()

()

.1

389-1	IDT	R 389-1—2011 «	- - 1. - - *
4869-1	MOD	12.4.211—99 (4869-1—89) «	- - »
60318-1	—	•	
60318-2	—	•	
60646-2	NEO	27072—86 «	- - »
* — 8 :			- -
- IDT — • MOD — • NEO —			

- (1) ISO 369-9:2009 Acoustics— Reference zero for the calibration of audiometric equipment — Part 9: Preferred test conditions for the determination of reference hearing threshold levels
- (2) HAN, LA. POULSEN, T. Equivalent threshold sound pressure levels for the SENNHEISER HDA200 headphone and the Etymotic Research ER-2 insert earphone in the frequency range 125 Hz to 16 kHz. *Scand. Audiol.* 27. 1998. pp. 105—112
- (3) RICHTER, U. Equivalent threshold sound pressure levels of the insert earphones Etymotic Research ER-2A and ER-4A in the extended high-frequency range. In: Richter, U.(ed.). Characteristic data of different kinds of earphones used in the extended high frequency range for pure-tone audiometry. PTB report PTB-MA-72. Braunschweig. 2003
- (4) TAKESHIMA, T., HIRAOKA, T., SUZUKI, Y., KUMAGAI, M and SONE, T. Reference equivalent sound pressure levels for new earphones. Proceedings of 15th international Congress on Acoustics. Trondheim, Norway. 1995. pp. 297—300
- (5) SCHONFELD, U., REUTER, W., FISCHER, R. and GROSS, M. Hearing thresholds of otologically normal subjects in the extended high-frequency range using the earphone HOA200. in: Richter, U.(ed.). Characteristic data of different kinds of earphones used in the extended high frequency range for pure-tone audiometry. PTB report PTB-MA-72. Braunschweig. 2003
- (6) KARLSEN, S. and LYDOLF, M. The performance of audiometric earphones on ear simulator and on human ears. *Acta Acustica united with Acustica*. submitted March. 2003
- (7) ISO 369-5:2006 Acoustics — Reference zero for the calibration of audiometric equipment — Part 5: Reference equivalent threshold sound pressure levels for pure tones in the frequency range 125 Hz to 16 kHz
- (8) ISO 8253-1. Acoustics — Audiometric test methods — Part 1: Basic pure tone air and bone conduction threshold audiometry

534.322.3.08:006.354

13.140

34

: , , , -

19.07.2012.

24.07.2012.

60 8 4

. . . 1.40. ' . . . 0.75. 94 . 47.

». 123995

.. 4.

www.gosbnfo.ru tn)o@gosbofo ru

« »

« » — . « ». 105062 . , .